


Materiaal: PE 100 (polyethyleen)

Uitvoering: PE buis met zwarte kleur, standaard met blauwe lijn.
Op aanvraag met bruine of gele lijn.

Klasse: SDR 11 - PN16

Normering: BENOR gecertificeerd tem DN500



| D (mm) | e _{min} | Kg/m | L (m) |
|--------|------------------|-------|--|
| 20 | 2 | 0,12 | Coil 200 / 300 m |
| 25 | 2,3 | 0,17 | Coil 100 / 200 / 300 m |
| 32 | 3 | 0,28 | Coil 100 / 200 / 300 m |
| 40 | 3,7 | 0,43 | Coil 100 / 200 / 300 m |
| 50 | 4,6 | 0,67 | Coil 100 / 200 / 300 m |
| 63 | 5,8 | 1,06 | Coil 100 / 200 / 300 m - Bar 6 / 12 / 13,5 m |
| 75 | 6,8 | 1,47 | Coil 100 / 200 m - Bar 6 / 12 / 13,5 m |
| 90 | 8,2 | 2,14 | Coil 100 m - Bar 6 / 12 / 13,5 m |
| 110 | 10 | 3,17 | Coil 100 m - Bar 6 / 12 / 13,5 m |
| 125 | 11,4 | 4,11 | Bar 6 / 12 / 13,5 m |
| 140 | 12,7 | 5,12 | Bar 6 / 12 / 13,5 m |
| 160 | 14,6 | 6,73 | Bar 6 / 12 / 13,5 m |
| 180 | 16,4 | 8,5 | Bar 6 / 12 / 13,5 m |
| 200 | 18,2 | 10,49 | Bar 6 / 12 / 13,5 m |
| 225 | 20,5 | 13,27 | Bar 6 / 12 / 13,5 m |
| 250 | 22,7 | 16,33 | Bar 6 / 12 / 13,5 m |
| 280 | 25,4 | 20,47 | Bar 6 / 12 / 13,5 m |
| 315 | 28,6 | 25,9 | Bar 6 / 12 / 13,5 m |
| 355 | 32,2 | 32,88 | Bar 6 / 12 / 13,5 m |
| 400 | 36,3 | 41,75 | Bar 6 / 12 / 13,5 m |
| 450 | 40,9 | 52,87 | Bar 6 / 12 / 13,5 m |
| 500 | 45,4 | 65,24 | Bar 6 / 12 / 13,5 m |
| 560 | 50,8 | 80,8 | Bar 6 / 12 / 13,5 m |
| 630 | 57,2 | 102 | Bar 6 / 12 / 13,5 m |